MG-525



Leather Softener Solution

1 Introduction:

MG-525 is an aqua based non-ionic leather softener solution for natural leathers such as cowhide and sheepskin, specially developed to soften the leather for stretching during production, making it less prone to splitting, cracking, and breakages.

MG-525 helps make the leather more obedient, without harm or discoloration, ideal to prevent time and material loss during last stages of production.

- * Excellent leather softener effect
- * Excellent smooth sense of touch
- * No harm to leather

2. Chemical-physical characteristics:

Appearance:	translucent liquid
Solidity (%):	3.5 +/- 0.5
Density (Kg/m3):	0.98 +/- 0.005
Thickness:	< 30

3. Available Colors:

MG-526 (Clear)

4. Application procedure:

MG-525 leather softener solution is a single liquid for simple application. Can be applied with cotton cloth or spray gun evenly throughout the leather surface and heat dry at 45°C - 55 °C for a more remarkable effect.

5. Storage:

The product may be stored in a place at a temperature below 40°C. Unopened packages have a life span of 5 year.

6. Package:

60L PE Drum (60 Kg)

Safety:

When handling this product the instructions set out in the safety data leaflet must be observed. The relevant safety and precautionary measures for hygiene in the workplace must also be followed when working with chemical products.

Observations:

The instructions given in this publication are based on the current stand of our knowledge and experience. This does not presuppose any judicial guarantee concerning certain properties nor their suitability for any application in particular. Given the many influences that may occur during the handling at use of our products, the persons handling or transforming them are not exempt from carrying out their own controls or tests. All those receiving our products will be responsible for observing all existing patent rights as well as all current laws and regulations.

More info: www.magicltd.com.tw

MAGIC LTD. (TAIWAN R.O.C.)

Tel. +886 4 2314 5686





